



## Lipstick 1

[View Details](#)

## Classification

Lipstick->Lipstic one

## Attributes

- 单卷毯: 80容重30mm厚(61cm宽\*1米长)
- 1111: ceshi
- 文档: [连衣裙资料](#)
- 品牌: pinpai1

## Specification

Size: S、M

## Product Description

Product Name: perfect diary / perfect diary... Brand: perfect diary / perfect diary product name: perfect diary wantonly outstanding velvet tube lipstick origin: China color classification: [new] Limited Edition L04 [new] Limited Edition L02 classic L01 [pre sale] classic L02 [pre sale] classic L03 classic L04 [pre sale] classic I05 [pre sale] classic L06 [pre sale] classic I07 [pre sale] classic I08 approval number: yueg makeup.com BZ 2020182829 efficacy: long term improvement of complexion and easy coloring specification type: normal specification for special purpose cosmetics: no time limit for use date range: 2023-09-27 to 2023-09-28





1



[fRpUfAKgsJlt.pdf](#)



[UpAUfKBfDcHM.pdf](#)

2



Model		KVF-12030-TDH	KVF-24030-TDH
Output	DC Voltage	12V/24V	24V
	Voltage Tolerance	±0.5V	
	Rated current	2.5A	1.25A
	Rated power	30W	
Input	Voltage Range	200-240VAC	
	Frequency Range	47~63HZ	
	Power Factor	PF≥0.97/200VAC PF≥0.97/230VAC PF≥0.97/240VAC(Full loading)	
	Full Load Efficiency(Typ.)	79%	79%
	AC Current (Max.)	0.22A	0.22A
	Leakage current	<0.50mA	
Protection	Short Circuit	shut down o/p voltage, re-power on to recover after fault condition is removed	
	Over Loading	≤ 120% shut down o/p voltage, re-power on to recover	
	Over Current	≤ 1.2 *I <sub>out</sub>	
	Over Temperature	100°C± 10°C shut down o/p voltage ,re-power on to recover	
Environment	Working TEMP.	-40~+70°C	
	Working Humidity	20-90%RH, non-condensing	
	Storage TEM.,Humidity	-40~+80°C,10-95%RH	
	TEMP.coefficient	±0.03%/°C(0-50°C)	
	Vibration	10-500Hz,2G 10min./1 cycle,period for 72min,each along X,Y,Z axes.	
Safety&EMC	Safety standards	EN61347-1 EN61347-2-13	
	Withstand voltage	I/P-O/P:3.75KVAC	
	Isolation resistance	I/P-O/P:100MΩ/500VDC/25°C/70%RH	
	EMC EMISSION	EN55015,EN61000-3-2,3 (≥ 60%loading)	
Others	Net.Weight	0.21KG	
	Size	155*54*20mm (L*W*H)	
	packing	160*60*23mm for inner box ; 350*240*130mm for carton 40PCS/CTN	
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input , rated load and 25°C of ambient temperature. 2. Tolerance: includes set us tolerance, line regulation and load regulation . 3. The power supply is considered as a component that will be operated in combination with final Equipment. Since EMC performance will be affected by the complete installation, the final equipment manufactures must be-qualify EMC Directive on the complete installation again 4. Loading range from 10% to 100%		

